



Spec of Business EVSE w/LCD



IP65 & IK10



7" LCD Screen



Fast to install



ISO15118-2(option)



Type 2 Plug



RFID(ISO / IEC14443 A/B)



OCPP1.6 J / 2.0.1 Upgradeable



3-layer housing for easy maintenance



LAN, Wi-Fi and Bluetooth Standard, 3G / 4G Optional

Model Name		CP300S	CP300E	CP300T
Power Specification	Input AC Rating	230Vac±10%	400Vac±10%	
	Input Max. AC Current	32A	16A	32A
	Frequency	50/60Hz		
	Max. Output Power	7kW	11kW	22kW
User Interface & Control	Display	7" LCD Screen		
	LED Indicator	Yes		
	User Authentication	RFID (ISO / IEC14443 A/B), APP		
Communication	Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G / 4G Optional		
	Communication Protocol	OCPP1.6 J / OCPP2.0.1 Upgradeable		
	Communication Function	ISO / IEC 15118 Optional		
Environmental	Operation Temperature	-30°C ~ 50°C		
	Humidity	5%~95% RH, Non-condensing		
	Altitude	≤ 2000m, No Derating		
Mechanical	IP/IK Level	IP65 / IK10		
	Cabinet Dimension (W×D×H)	245mm × 121.47mm × 365mm		
	Weight	6.52kg	6.68kg	6.72kg
	Cable & Plug	5m(Standard), 7m(Optional)		
Protection	Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection), Control Pilot Fault, Relay Welding Detection, RCD(DC 6mA)		
Regulation	Safety	IEC 61851-1, IEC 61851-21-2		
	Certificate	CE, CB, UKCA, TR25 and RCM		
	Charging Interface	IEC 62196-2 Complaint, Type 2 Plug		