



IP66 & IK10



7" LCD Screen



Anti-theft Housing Design



ISO15118-2 (option)



Type 2 Plug / Socket



RFID (ISO / IEC14443 A/B)



OCPP1.6 J / 2.0.1 Upgradeable



3-layer housing for easy maintenance



LAN, Wi-Fi and Bluetooth Standard, 3G / 4G Optional

Model Name		CP308S	CP308E	CS308T
Power Specification	Input AC Rating	230Vac±10%	400Vac±10%	
	Input Max. AC Current	32A	16A	32A
	Frequency	50/60Hz		
	Max. Output Power	7kW	11kW	22kW
User Interface & Control	Display	7" LCD Screen		
	LED Indicator	Yes		
	User Authentication	RFID (ISO / IEC14443 A/B), APP		
Communication	Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G / 4G Optional		
	Communication Protocol	OCPP1.6 J / OCPP2.0.1 Upgradeable		
Environmental	Operation Temperature	-30°C ~50°C		
	Humidity	5%~95% RH, Non-condensing		
	Altitude	≤ 2000m, No Derating		
Mechanical	IP / IK Level	IP54 / IK10		
	Cabinet Dimension (W×D×H)	313mm × 157mm × 451mm		
	Weight	5.32kgs	5.59kgs	5.69kgs
Protection	Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection), Control Pilot Fault, Relay Welding Detection, RCD(DC 6mA)		
Regulation	Safety	IEC 61851-1, IEC 61851-21-2		
	Certificate	CE, CB, UKCA		
	Charging Interface	IEC 62196-2 Complaint, Type 2 Socket		